



宁波图信通讯设备有限公司
Ningbo Tuxin Communication Equipment Co.,Ltd.

Descriptions

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.

Model Number: TX-IEC-20C13+4C19-2P-VC-1.5U

Category: Basic

Sub Category: Standard

Power Configuration: 32A, 230V, 7.3kW

Physical Configuration: 1410mm x 45mm x45mm , Vertical , Bottom power input, power locking mechanism

Product Summary: Basic Standard, 32A, 230V, 7.3kW, Vertical, (20) IEC C13, (4) IEC C19, Breakered, 3m power cord 2P+E (IP44), Black Powder Coat

Plug Form:



2P + E
(IP44)

Receptacle:



IEC C13
(Quantity:20)



IEC C19
(Quantity:4)

Chassis Color Options:





宁波图信通讯设备有限公司

Ningbo Tuxin Communication Equipment Co.,Ltd.

System Features

Display screen	Voltage and current
Voltage	220-240V
Current	32A
VA per Input (Load Capacity)	7.3kW (230V)
Frequency	50/60Hz
Over Current Protection	(2) 16A Single Pole Magnetic Breakers
Switch	Breaker/Switch Combination
Power Cable Wire Gauge	3x6mm ² H05VV-F
Power Cable Type	3m length; Male Plug
Plug Type	IEC60309 2P + E, 32A, 250V, Splash proof IP44
Receptacle/Socket Type #1	IEC320 C13
- Quantity	20
- Quantity per Breaker	10
- Maximum Output per Receptacle/Socket	10A
- Voltage per Receptacle/Socket	230V
Receptacle/Socket Type #2	IEC320 C19
- Quantity	4
- Quantity per Breaker	2
- Maximum Output per Receptacle/Socket	16A
- Voltage per Receptacle/Socket	230V
Maximum Operating Temperature	0 ~ 45°C/113F
Heavy Steel - Powder Coat Finish	Black
Configuration	1U, Vertical
Product Warranty	2 years
Certification/Agency Approvals	CE, RoHS
Chassis Dimensions (HxWxD)	1410mm x 45mm x 45mm